







Vectra S2

≋'

ጠ

Flow: 1,400 gph (5,300 lph)

Max Head Pressure: 11.5 feet (3.5m)

Footprint: 3.8 x 6.5in (98.4 x 165.4mm)

Fittings: ANSI Input: 1in Output: 0.75in Metric Input: 32mm Output: 25mm



Vectra M2

Flow:
2,000 gph (7,500 lph)



Max Head Pressure: 21.5 feet (6.5m)

Footprint: 4.5 x 7.5in (113.5 x 192.6mm)



ANSI Input: 1.25in Output: 1in Metric Input: 40mm Output: 32mm



Vectra L2



Flow: 3,100 gph (11,500 lph)

Max Head Pressure: 21.5 feet (6.5m)



Footprint: 5 x 8.5in (126.8 x 215.15mm)

Fittings: ANSI

Input: 1.5in Output: 1.25in Metric Input: 50mm Output: 40mm

) mobius[™]

Mobius Driven

Aquarium equipment control as it should be. Get the free app or learn more at mobius.app

Functions



Closed Loop Mode



Mode



Quiet Operation



Flow Calibration



Mobius Compatible



Í

iOS Compatible



Android Compatible

Accessories

Battery Backup

Continue your tank's flow for up to 60 hours in the case of a power outage or interruption.

Power Supply Bracket

Mount your Vectra Power Supply safely and neatly out of the way while maintaining ease of access for maintenance.

Fittings

Additional input and output Basket and Barb fittings are available for further customization.

Driver Bracket

Mount your Vectra driver securely while maintaining ease of access for programming and adjustment.